

**HIGH TEMPLE WORKSHOP 22**  
**21 – 24 JANUARY, 2002, Santa Fe, New Mexico**

Presentation Title: “Evaluation of Graphite Fiber/Polyimide PMCs from Hot Melt vs Solution Prepreg”

Authors: E. Eugene Shin<sup>1</sup>, James K. Sutter<sup>2</sup>, Howard Eakin<sup>2</sup>, Linda Inghram<sup>1</sup>, Linda McCorkle<sup>1</sup>, Dan Scheiman<sup>3</sup>, Demetrios Papadopoulos<sup>4</sup>, John Thesken<sup>1</sup> --- *NASA Glenn Research Center, 21000 Brookpark Rd., Cleveland, OH 44135*

<sup>1</sup> Contract via. OAI; <sup>2</sup> C/S NASA; <sup>3</sup> Contract via. QSS; <sup>4</sup> Contract via. U. of Akron;

Jeffrey E. Fink --- *Boeing-Rocketdyne Division, 6633 Canoga Park Av, MS AC-67, Canoga Park, CA 91309-7922*

Submitted by: E. Eugene Shin

Address: Ohio Aerospace Institute - NASA Glenn Research Center  
21000 Brookpark Rd., MS 49-1  
Cleveland, Oh 44135  
Tel: 216-433-2544, Fax: 216-977-7132  
E-mail: [E.Eugene.Shin@grc.nasa.gov](mailto:E.Eugene.Shin@grc.nasa.gov)

## ABSTRACT

Carbon fiber reinforced high temperature polymer matrix composites (PMC) have been extensively investigated as potential weight reduction replacements of various metallic components in next generation high performance propulsion rocket engines. The initial phase involves development of comprehensive composite material-process-structure-design-property-in-service performance correlations and database, especially for a high stiffness facesheet of various sandwich structures. Overview of the program plan, technical approaches and current multi-team efforts will be presented. During composite fabrication, it was found that the two large volume commercial prepregging methods (hot-melt vs. solution) resulted in considerably different composite cure behavior. Details of the process-induced physical and chemical modifications in the prepregs, their effects on composite processing, and systematic cure cycle optimization studies will be discussed. The combined effects of prepregging method and cure cycle modification on composite properties and isothermal aging performance were also evaluated.

This is a preprint or reprint of a paper intended for presentation at a conference. Because changes may be made before formal publication, this is made available with the understanding that it will not be cited or reproduced without the permission of the author.